Wet End - Process Formulation (RETAN)



N°28 BOREALE.xlsx		Date:	15-Feb-2024
		Technician:	LL.S /J.C.P
Company:	TFL AW 2025-2026	TFL	
Type of Leather:	Shoe Upper & Leather Goods	Trial - N°:	WE 02/2024
Aim of Trial:		Color:	tpx 18-4936
		Piece count:	6 sides
Project - N°:	art. BOREAL	Substance:	1,2-1,3 mm
Material:	WB HOLLAND	Weight:	
% refer to:	SHAVED	Drum - N°:	

Operation	Add	%	Weight in kg	Product	Temp. in °C	Dilution (1 : x)	Time in min	Control
			ng		0	(112)		
		200,00		water	30			
		0'2		BORRON® SAF				
		0'2		oxalic acid			30´	
DRAIN		02		Oxano dola			- 00	
		100,00		water	30			
		2,00		CORIPOL® SLG (1:3)	- 00		20´	
		4,00		SELLATAN® WLG (1:3)			30´	
		4,00		BLANCOROL® RC			90′	autom. O.N 5' x 30'
DRAIN	++	7,00		DESTRUCTION NO.				22.0111 011 0 X 00
DIGHT	++	150,00		water	30			
		2,00		SELLASOL® NG liq	30		20´	
		1,50		Sodium formate			20´	
		0,50		Sodium bicarbonate (1:3)			20´	
	+++	2,00		LEVOTAN® L			60´	pH 5.5
DRAIN	+++	2,00		LEVOTAN			00	ρι τ σ.σ
DIVAIN	+++	100,00		water	30			
	+++	10,00		SELLATAN® RLS	30		30´	
		6,00		LEVOTAN® HPP	+		30	
		4,00		SELLASOL® BC7	+		20´	
		6,00		LEVOTAN® AT			20´	
		5,00		SELLATAN® TMC			30´	
	++			SELLASOL® TN				
	++	1,00					30′	
		1,25		SELLA® Fast Green MG			4=4	
		1,25		SELLA® Fast Blue LN			45´	
	+	50,00		water	50			
	\rightarrow	8,00		LEVOTAN® HPP				
		1,00		CORIPOL®SLG (1:3)				
	\perp	2,00		CORIPOL® ALF		ļ	45´	
	\perp							
		1,00		Formic acid			20′	
	\dashv	1,00		Formic acid			20´	
DRAIN	\perp							
	1 1	200,00		water	20	1	10´	

Mechanical Operation: samming/setting out/ vacum 45°c 90 sec./ hang to dry/ conditioning/staking Process Information:

Running Time:

Our application recommendations are in line with our present state of knowledge. They do not, however, exempt the customer fr om performing his own tests to determine the suitability of the supplied products for their intended purposes. Application of the products lies outside the scope of our control and therefore comes w ithin the customer's sphere of responsibility. We guarantee the satisfactory quality of our products subject to general terms of sale and delivery.

Above data are based on the current state of knowledge. However, buyer is not released from his obligation to examine the mat erial on receipt. Seller makes no warranty of merchantability or fitness for practical use or application..