| N°9 KIMONO WET END.xlsx |                          |                |        |                         |       |          |        | 8-Jan-2024      |  |
|-------------------------|--------------------------|----------------|--------|-------------------------|-------|----------|--------|-----------------|--|
|                         |                          |                |        |                         |       |          | cian:  | Tempes          |  |
| Company:                | TFL                      |                |        |                         |       |          |        | •               |  |
| Type of Leather:        |                          |                |        |                         |       |          | l°:    |                 |  |
| Aim of Trial:           |                          |                |        |                         |       |          |        | 15-114          |  |
|                         |                          |                |        |                         |       |          | ount:  | [               |  |
| Project - N°:           | 9 KIMONO                 |                |        |                         |       |          | nce:   | 1,1-1           |  |
| Material:               | calf wb<br>shaved weight |                |        |                         |       |          |        |                 |  |
| % refer to:             |                          |                |        |                         |       |          | N°:    |                 |  |
|                         |                          |                |        |                         |       |          |        |                 |  |
| Operation               | Add                      | %              | Weight | Product                 | Temp. | Dilution | Time   | Control         |  |
|                         |                          |                | in kg  |                         | in °C | (1 : x)  | in min |                 |  |
|                         |                          | 300,00         |        | water                   | 40°C  |          |        |                 |  |
|                         |                          | 1,00           |        | formic acid             |       |          |        |                 |  |
|                         |                          | 0,50           |        | PELTEC <sup>®</sup> ADN |       |          | 30     |                 |  |
| drain                   |                          | 100.00         |        |                         |       |          |        |                 |  |
|                         |                          | 100,00         |        | water                   | 40°C  |          |        |                 |  |
|                         |                          | 2,00           |        | CORIPOL® DX1202         |       |          |        |                 |  |
|                         |                          | 4,00           |        | RETINGAN® RLF           |       |          | 30     |                 |  |
|                         |                          | 5,00           |        | TANNESCO® HN            |       |          | 00     |                 |  |
|                         | + $+$                    | 5,00           |        | CHROMOSAL® B            |       | <b> </b> | 60     | outomotic       |  |
| duala                   | + $+$                    | 2,00           |        | sodium formate          |       |          | 120    | automatic       |  |
| drain                   | + $+$                    | 150.00         |        | water                   | 35°C  |          |        | morning pH: 3,8 |  |
|                         | + $+$                    | 150,00<br>3,00 |        | SELLASOL® NG liq.       | 30 C  |          |        |                 |  |
|                         | + $+$                    | 3,00           |        | sodium formate          |       |          | 30     |                 |  |
|                         |                          | 0,30           |        | sodium bicarbonate      |       |          | 30     |                 |  |
|                         |                          | 4,00           |        | LEVOTAN L               |       |          | 40     | pH: 4,6-4,8     |  |
| drain wash              |                          | 4,00           |        |                         |       |          | 40     | pii. 4,0-4,0    |  |
|                         |                          | 100,00         |        | water                   | 30°C  |          |        |                 |  |
|                         | + $+$                    | 1,00           |        | MAGNOPAL® DP            |       | +        | 5      |                 |  |
|                         |                          | 5,00           |        | BAYTIGAN® AR            |       |          | 30     |                 |  |
|                         |                          | 5,00           |        | LUBRITAN® SPE           |       |          | 20     |                 |  |
|                         | +                        | 0,00           |        |                         |       |          |        |                 |  |

|                   |                   |                                   | Running Til | 9 hrs 45 min |  |
|-------------------|-------------------|-----------------------------------|-------------|--------------|--|
| set out, vacuum o | dry 180'' at 40°C |                                   |             |              |  |
| Mechanical Ope    |                   | Process Information:              |             |              |  |
| uialii            |                   |                                   |             |              |  |
| drain             | 0,50              | formic acid                       |             | 20           |  |
|                   | 6,00              | LEVOTAN® RP                       |             | 30           |  |
|                   | 0,40              | BORRON® SAF                       |             | 60           |  |
|                   | 4,00              | CORIPOL® WKN                      |             |              |  |
|                   | 6,00              | CORIPOL® DX1202                   |             |              |  |
|                   | 100,00            | water                             | 50°C        |              |  |
| drain wash        |                   |                                   |             |              |  |
|                   | x                 | formic acid                       |             | 30           |  |
|                   | 100,00            | water                             | 50°C        |              |  |
|                   | 5,00              | RETINGAN <sup>®</sup> R7          |             | 60           |  |
|                   | x                 | SELLA <sup>®</sup> Fast dyestuffs |             |              |  |
|                   | 2,00              | TANIGAN <sup>®</sup> SR           |             | 20           |  |
|                   | 4,00              | SELLASOL® FTF                     |             |              |  |
|                   | 3,00              | TANIGAN <sup>®</sup> PURE T-A     |             |              |  |
|                   | 9,00              | TANIGAN <sup>®</sup> MBO liq.     |             |              |  |
|                   | 5,00              | LUBRITAN® SPE                     |             | 20           |  |
|                   | 5,00              | BAYTIGAN® AR                      |             | 30           |  |
|                   | 1,00              | MAGNOPAL® DP                      | 000         | 5            |  |

Our application recommendations are in line with our present state of knowledge. They do not, however, exempt the customer fr om performing his own tests to determine the suitability of the supplied products for their intended purposes. Application of the products lies outside the scope of our control and therefore comes w ithin the customer's sphere of responsibility. We guarantee the satisfactory quality of of our products subject to general terms of sale and delivery. Above data are based on the current state of knowledge. However, buyer is not released from his obligation to examine the mat erial on receipt. Seller makes no warranty of merchantability or fitness for practical use or application.