## **Tanning**





% based on fleshed weight VESSEL **trial drum** weight: **5** kg TECHNICIAN **ACI TEAM** 

weight.	3	ĸg		TECHNICIAN	l	ACI TEAIVI
Process	%	kg	Product	Run	Stop	Comments
	60	3	Water,35 ℃			
	6	0,3	Salt	10'		Bé 6.5-7.0
DE DIGITINO		0.075		2*401.201		
DE-PICKLING	1,5	0,075	Sodium formate	2*10'+30'		
	0,75	0,0375	Sodium bicarbonate	3*10'+45'		Check ph: 4.8-5.0
	0,5	0,025	OROPON® DVP			
DEGREASING	0,5	0,025	PELTEC® AD-N			
	0,5	0,025	BORRON® SE	90'		Check for proper degreasing
Drain						
	200	10	Water,35 °C	10'		
Drain						
	60	3	Water,35 °C			
	6	0,3	Salt	10'		Bé 6.5-7.0
	0,5	0,025	MAGNOPAL® IPF	20'		
	0,5	0,025	Formic acid	2*10'+10'		
	0,5	0,025	PRODUCT® F 4142	30'		
	0,5	0,025	Formic acid	2*10'+30'		Check ph: 2.8-3.0 in BCG to Yellow
TANNING						
	4	0,2	SELLATAN® G50-I	180'		Automatic over night next day run for 10'
	0,5	0,025	Sodium acetate	30'		
	10	0,5	TANIGAN® MB-O LIQ			
	1	0,05	PRODUCT® F 4142	90'		
BASIFICATION	0,5	0,025	SELLASOL® PAK-I	2*10'+45'		Check ph: 4.0-4.2
Drain	0,5	0,023	JELLAJUL FAR-I	2 10 143		CICCR pii. 7.0 7.2
	200	10	Water,35 °C	10'		
Drain			<i>,</i>			
	200	10	Water,35 °C			
	0,1	0,005	BORRON® ST			
	0,1	0,005	Preservative	20'		
Drain	-	-				

Keep ageing for 2 -3 days and check for any area shrinkage,do samm and wet buffing if needed for further processing...

## Comments:

ARACIT®, BORRON®, CORIPOL®, CROMENO®, DERMASCAL®, ERHA®, ERHAVIT®, MAGNOPAL®, OROPON®, PELLVIT®, SELLASOL®, SELLATAN® and TANNESCO® are registered or filed trademarks, owned by or licensed to TFL in most countries.

Our application recommendations are in line with our present state of knowledge. They do not, however, exempt the customer from performing his own tests to determine the suitability of the supplied products for their intended purpose. Application of the products lies outside the scope of our control and therefore comes within the customer's sphere of responsibility.

We guarantee the satisfactory quality of our products subject to our general terms of sale and delivery.