## Wet End - Process Formulation (BEAMHOUSE)

|                  |                                 | Date:            | 11-Jan-2023  |  |
|------------------|---------------------------------|------------------|--------------|--|
|                  |                                 | Technician:      | ACITEAM      |  |
| Company:         | IILF 2024                       | Score:           | Select Score |  |
| Type of Leather: | SHEEP WASHABLE GARMENT NAPPA    | Recipe Code:     | ACI23526BH   |  |
| Aim of Trial:    | Sheep chrome tanning - Washable | Batch N°:        |              |  |
| Material:        | Sheep Raw - Imported            | Piece Count:     | 15           |  |
| % refer to:      | Salted weight                   | Drum N°:         |              |  |
| Drum Type:       | √ Standard Drum                 | Weight (kg):     | 36 kg        |  |
|                  | Jumbo / Y-Drum                  | Cold Water (°C): | 30 °C        |  |

| ٥ | Operation      | Add    | %      | Weight | Product                                  | Temp. | Dilution            | Run      | Rest     | Repeat  | Control                         |
|---|----------------|--------|--------|--------|--|-------|---------------------|----------|----------|---------|---------------------------------|
| 8 |                |        | 050.00 | in kg  |  | in °C | (1 : x)             | in min   | in min   | x-times |                                 |
| Ļ | Presoak        |        | 250,00 | 90,000 | water                                    | 38    |                     | 40       | 00       |         |                                 |
| ļ |                | +      | 0,10   | 0,036  | Aracit® Z-L                              |       |                     | 10<br>15 | 30<br>45 |         |                                 |
| ŀ | Drain          |        |        |        |  |       |                     | 15       | 45       |         |                                 |
| t |                |        |        |        |  |       |                     |          |          |         |                                 |
| T | MainSoak       |        | 150,00 | 54,000 | water                                    | 32    |                     |          |          |         |                                 |
| T |                | +      | 0,30   | 0,108  | Pelvit® IS-A                             |       |                     | 20       | 30       |         |                                 |
| I |                |        | 0,30   | 0,108  | Blancorol® BA-IN                         |       |                     | 20'      | 30'      |         | PH-9.5                          |
| ŀ |                |        | 0,25   | 0,090  | Peltec® X-Zyme SLR                       |       |                     |          |          |         |                                 |
| ł |                | -      | 0.05   | 0.018  | Aracit® Z-L                              |       |                     |          |          |         |                                 |
| ł |                | _      | 0,03   | 0,016  | Peltec® AD-N                             |       |                     | 180'     |          |         | automatic                       |
| ł | Drain          | _      | 0,10   | 0,030  | Fellec® AD-IN                            |       | -                   | 100      |          |         | go green fleshing               |
| ł | Diaili         | _      | 10,00  | 3,600  | water                                    | 30    |                     |          |          |         | pH:7-8,09                       |
| ╀ | Paste liming   | +      | 2,00   | 0,720  | Lime powder                              | 30    |                     |          |          |         | рп.7-0,09                       |
| P | Paste iiming   | - +    | 1,50   | 0,720  | Sodium sulphide flakes                   |       |                     |          |          |         |                                 |
| Ł |                |        | 1,50   |        |  |       |                     |          |          |         |                                 |
| Ł |                |        | 4,00   | 1,440  | Erhavit® LSR                             |       |                     |          |          |         |                                 |
| Ł |                |        | 0,50   | 0,180  | Erhavit® LSC                             | _     |                     |          |          |         | make a paste                    |
| Ł |                |        |        |        |  | -     |                     |          |          |         | Be; 25-26                       |
| Ļ |                | _      |        |        |  |       |                     |          |          |         | Apply flesh side                |
| ļ |                |        |        |        |  |       |                     |          |          |         | Ageing for 4 hrs                |
| Ļ | 5              |        | 400.00 |        |  | 0.0   |                     |          |          |         | after ageing 90% of hair remove |
|   | Reliming       |        | 100,00 | 36,000 | water                                    | 30    |                     |          |          |         |                                 |
| L |                |        | 1,00   | 0,360  | Lime powder                              |       |                     |          |          |         |                                 |
| L |                | +      | 1,00   | 0,360  | Peltec® UAC                              |       |                     |          |          |         |                                 |
| L |                |        | 0,50   | 0,180  | Erhavit® LSU                             |       |                     | 30       | 30       |         |                                 |
| L |                |        |        |        |  |       |                     |          |          |         |                                 |
| L |                | +      | 0,50   | 0,180  | Lime                                     |       |                     |          |          |         |                                 |
| L |                |        | 0,50   | 0,180  | Erhavit® LSR                             |       |                     |          |          |         |                                 |
| L |                | +      | 0,10   | 0,036  | Erhavit® LSC                             |       |                     | 30       | 30       |         | automatic                       |
| L |                |        |        |        |  |       |                     |          |          |         | run for 5' every 1 hr           |
| L |                |        |        |        |  |       |                     |          |          |         | do fleshing next day            |
| L |                |        |        |        |  |       |                     |          |          |         | ph:11.0                         |
|   |                |        |        |        |  |       |                     |          |          |         |                                 |
|   |                | 1      |        |        |  |       |                     |          |          |         |                                 |
| Í |                |        |        |        |  |       |                     |          |          |         |                                 |
| ļ |                | +      |        |        |  |       |                     |          |          |         |                                 |
|   |                |        |        |        |  |       |                     |          |          |         |                                 |
|   |                |        |        |        |  |       |                     |          |          |         |                                 |
| e | chanical Opera | ation: |        |        |  | Proce | ss Inform           | ation:   |          | L       |                                 |
| 3 |                |        |        |        |  |       | Total Process Time: |          |          |         | #BEZU                           |
|   |                |        |        |        | Running Time:                            |       |                     | #BEZUG!  |          |         |                                 |
|   |                |        |        |        | Water Consumption:<br>Energy, Hot Water: |       |                     | #BEZUG!  |          |         |                                 |
|   |                |        |        |        |  |       |                     |          |          |         |                                 |
|   |                |        |        |        |  |       | y, Drive:           |          |          |         | #BEZUC                          |

Running Time: Water Consumption: Energy, Hot Water: Energy, Drive: Our application recommendations are in line with our present state of knowledge. They do not, however, exempt the customer from performing his own tests to determine the suitability of the supplied products for their intended purposes. Application of the products lies outside the scope of our control and therefore comes within the customer's sphere of responsibility. We guarantee the satisfactory quality of our products subject to general terms of sale and delivery.

Above data are based on the current state of knowledge. However, buyer is not released from his obligation to examine the material on receipt. Seller makes no warranty of merchantability or fitness for practical use or application.