Wet End - Process Formulation (RETAN)

ΓFL	

13 hrs 10 min

N°13 PANTO WET END.xlsx		Date:	5-Jul-2023
		Technician:	
Company:	<u>TFL</u>	Score:	Select Score
Type of Leather:	Shoe Upper & Leather Goods	Trial - N°:	
Aim of Trial:	PANTO	Color:	
		Piece count:	
Project - N°:		Substance:	1,2/1,4
Material:	WET-BLUE	Weight:	
% refer to:	Shaved	Drum - N°:	

Operation	Add	%	Weight	Product	Тетр.	Dilution	Time	Control
			in kg		in ℃	(1 : x)	in min	
		200,00		Water	35			
		0,30		Formic Acid		10	40	pH:
Drain								
		100,00		Water	35			
		4,00		TANNESCO HN Liq				
		2,00		Chrome 33			120	pH:3,8/4,0
	+	2,00		SELLASOL NG GRAN				
		2,00		Sodium Formate			30	
		0,80		Sodium Bicarbonate			30	
		2,00		LEVOTAN L				
	+	2,00		MAGNOPAL DP		3	90	pH; 5,0/5,5
)rain		_,-,-						p, 0,0,0,0
, and		200,00		Water	30		10	
rain	+	200,00			30		10	
ri uiii		50,00		Water	30			
		2,00		BAYKANOL TF-2N CO1	30		10	
	+	2,00		SELLA FAST		10	30	
	+	3,00		LEUKOTAN 1093		3	30	
	T .	6,00		MAGNOPAL PGN		3		
		4,00		LEVOTAN L			30	
	+	10,00		TANIGAN MB-O LIQ			30	
	+							
		4,00		Chestnut			20	
		4,00		RETINGAN Pure RS			30	
	+	2,00		TANIGAN PR				
				SELLA FAST				
		2,00		SELLA FAST		10	90	
	+	100,00		Water	50		10	
	+	8,00		LEVOTAN XB				
		2,00		LEVOTAN WS		4	60	
	+	0,80		Formic Acid		10	20	
	+	0,80		Formic Acid		10	20	
	+	0,80		Formic Acid		10	20	pH: 3,4/3,6
Drain								
		200,00		Water	30		10	
Drain								
		150,00		Water	30			
		1,00		LEVOTAN WS		4	30	
	+	4,00		chrome 33			90	
Drain		,						
		200,00		Water	30		10	
Drain		3-2,2-3			33			
	1 1	200,00		Water	30		10	
Drain	1 1	_ 50,00			30			
				+				
	+++							
	+			+				
Mechanical Opera					Dec ages 1	formation:		L
vicenumeur Oper	acion.				FI OCESS III	joi macion:		

Running Time:

Our application recommendations are in line with our present state of knowledge. They do not, however, exempt the customer from performing his own tests to determine the suitability of the supplied products for their intended purposes. Application of the products lies outside the scope of our control and therefore comes within the customer's sphere of responsibility. We guarantee the satisfactory quality of our products subject to general terms of sale and delivery.

Above data are based on the current state of knowledge. However, buyer is not released from his obligation to examine the material on receipt. Seller makes no warranty of merchantability or fitness for practical use or application.